



Operating information for MEIER swimming pool covers

With the Meier pool cover you have purchased a product of top international quality. To ensure that you enjoy your Meier pool cover for many years to come, the following points must be observed:

The roller shutter is a protective device. Entering and swimming underneath this is prohibited. The roller shutter is impact resistant. Nevertheless, it is advisable not to throw any solid or sharp objects on to the shell.

Checking the water level before opening and closing the roller shutter:

The water level must be within the permitted tolerance. The roller shutter shell must not touch either the side support (handrail, wall offset) or the bordering stones. Replace any loss of water if necessary. Drain any excess water (e.g. after a heavy thunderstorm).

Opening:

Check the surface of the roller shutter before opening. No objects must be present on the roller shutter (branches, toys, etc.). Stay at the switch while opening. In case of unforeseen events, the roller shutter should be stopped immediately. Locate problem and fix if possible, otherwise contact your local swimming pool company.

The swimming pool may only be used when the pool cover is completely open.

Closing:

The water surface must be calm. No persons may remain in the pool. Balls, air mattresses, toys etc. are to be removed. Entry ladder, circulating system, vacuum cleaner are to be dismantled if necessary. After checks have been carried out, the roller shutter can be closed. Stay close to the switch while closing. In case of unforeseen events, the roller shutter should be stopped immediately. Locate problem and fix if possible. Then open the pool again completely. Close the pool as usual. In case of problems that cannot be solved, please contact your swimming pool company.

Work on the swimming pool cover must never be carried out inside the pool or standing in the water. This must only be carried out by qualified personnel.

Swimming under the cover is life threatening and prohibited under all circumstances!

Stepping on the roller shutter may only occur in an emergency.



Maintenance and care for MEIER swimming pool covers

Profiles made of PVC (Poly-Vinyl-Chloride) material are best cleaned using the high-pressure cleaner at max. 40 ° Celsius (water temperature), in addition you may also special Alkasal cleaner Kalfort (against lime). ATTENTION! Profiles made of PC (poly-carbonate) material may only be cleaned with the high-pressure cleaner and water at a maximum water temperature of 80 ° Celsius. All other types of cleaning or cleaning agents damage the profiles and cause cracks. Polycarbonates lose their resistance when steam-sterilised or treated with alkaline detergent. Please also observe their water treatment in this regard!

The underside of the roller shutter is cleaned by the circulating pool water and can not pollute when water circulation is working.

Important: In principle, every Meier pool cover must be protected from direct sunlight (even short term) when not lying on the water. Overheating can cause deformations and burns of the slats.

Maintenance of the engine system

The engines are permanently lubricated. Any adhering dirt (leaves, cobwebs, dust) must be removed from the motor and chain drive. The chain from the engine and the hand crank must be tensioned and lubricated at regular intervals. The system must be disconnected from the mains when this work is carried out.

Winter operation

During winter operation, some points should be noted, as cold temperatures can affect the mechanical / physical properties of the entire system.

- The pool cover can be left on the water, but the water should not fall below a temperature of 5 ° Celsius in order to avoid a larger accumulation of snow. Larger accumulations of snow (more than 20cm) must be cleared up immediately.
- The swimming pool cover must not be moved as frost can damage the mechanical parts.
- Leaves and foliage must be removed from the cover, as the foliage's yellow acidity can cause discoloration and defects on the cover.
- For underfloor systems, the swimming pool cover may also remain rolled up in the shaft, but must remain protected from sunlight, dirt and frost.
- In the case of above-ground installations, the system can be rolled up, protected from sunlight and kept in isolation over the winter.

All information is compiled with great care without, however, guarantee of accuracy. A liability or guarantee for topicality, correctness and completeness of the reproduced information and data are excluded. We reserve the right to amend or make additions to the information or data already provided without notice. Under no circumstances will liability for damages resulting from the use of the information supplied be assumed.

We cannot assume any liability for damages due to inappropriate treatment of the pool cover. Warranty claims must be rejected.

